APPROVAL SHEET

FOR

PIEZO BUZZER

ILOSAM ELECTRONICS CO., LTD.

CLUE No.:

OUR PART No.:

MODEL No.: ITH-2015PC

CUSTOMER PART No.:

DOCUMENT No.:

CUSTOMER	APPROVED	CHECKED

1. Document revision history

修改时间	版本	修改页次	修改内容	确认人
2021-08-31	A0	Pag.1	料号变更，原 017-2270B-20277 升级为 017-2270-01	唐瑜靖

2. Technical Parameter

Measuring condition


Part shall be measured under a condition (Temperature: 5～35℃, Humidity: 45%～85%R.H., Atmospheric pressure: 860 ～1060hPa) unless the standard condition (Temperature: 25±3℃, Humidity: 60±10%R.H. Atmospheric pressure: 860 ～1060hPa) is regulated to measure.



1	Resonant Frequency	4000Hz
2	Operating Voltage	1～25 Vp-p
3	Rated Current	Max.5mA , At 4KHz 50% duty Square Wave 9Vp-p
4	Sound Output at 10cm	Min.85dB, At 4KHz 50% duty Square Wave 9Vp-p
5	Capacitance	25000±30% pF At 1KHz
6	Operating Temperature	-20℃～+70℃
7	Store Temperature	-30℃～+80℃
8	Net Weight	Approx 1g
9	RoHS	Yes

3. Dimensions

Unit: mm




*Unit: mm; Tolerance: ±0.5mm Except Specified

*Housing Material: Black PPO (V1 防火)


4.Electrical And Acoustical Measuring Condition

Recommended Setting



测试示意图

5.Frequency Response



9Vp-p 50% duty Square wave,10cm

6. Reliability Test

After any following tests the part shall meet specifications without any degradation in appearance and performance except SPL. SPL shall not deviate more than -5 dB from the initial value

6.1 Ordinary Temperature Life Test

The part shall be subjected to 96 hours at 25±10℃. Input rated voltage Resonant frequency, 1/2 duty Square wave.

6.2 High Temperature Test

The part shall be capable of with standing a storage temperature of +70℃ for 96 hours.

6.3 Low Temperature Test

The part shall be capable of with standing a storage temperature of -30℃ for 96 hours.

6.4 Humidity Test

Temperature:+40℃±3℃ Relative Humidity:90%～95% Duration: 48 hours and expose to room temperature for 6 hours

6.5 Temperature Shock Test

Temperature:60℃ /1hour→ 25℃/3hours→-20℃/1hour→ 25℃/3hours (1cycle)
Total cycle: 10 cycles

6.6 Drop Test

Standard Packaging From 75cm(Drop on hard wood or board of 5cm thick, three sides, six plain.)

6.7 Vibration Test

Vibration:1000cycles /min. Amplitude:1.5mm, Duration: 1 hour in each 3 axes

Note:

As this product is not protected from foreign material entering, please make sure that any foreign materials (e.g. magnetic powder, washing solvent, flux, corrosive gas) do not enter this product in your production processes. The functional degradation (e.g. SPL down) may occur if foreign material enter it.

7.Packing		
包装要求	1. 珍珠泡棉板 50PCS/板 料号：F6-G-027 2. 内盒 500PCS/盒 料号：F6-H-009/ F6-H-010 3.外箱 2000PCS/箱 料号：F6-X-012	
唛头要求		

